

## HART TRANSPARENT DRIVER 9107A

Apart from the data listed below, the 9107A is identical to the 9107B. For all other data and functionality, please refer to the manual for 9107B.

**Applications:**

The 9107A can be mounted in and transmit signals to non-classified area and zone 2.

**Approvals:**

EMC 2004/108/EC . . . . . EN 61326-1  
 LVD 2006/95/EC . . . . . EN 61010-1  
 c UL us, Standard for Safety . . . . . UL 61010-1  
 EAC

**Ex:**

ATEX/94/EC. . . . . PR 14ATEX0101 X

**Marine:**

Det Norske Veritas, Ships & Offshore. . . . . Standard for Certification No. 2.4

**Functional Safety:**

SIL 2 Certified & Fully Assessed acc. to IEC 61508

**Order**

| Type         | Unit channels |
|--------------|---------------|
| <b>9107A</b> | Single : A    |
|              | Double : B    |

**Accessories**

| Type        | Description                        |
|-------------|------------------------------------|
| <b>4501</b> | Display / programming front        |
| <b>4511</b> | Communication enabler              |
| <b>9400</b> | Power rail                         |
| <b>9404</b> | Module stop for rail               |
| <b>9410</b> | Power control unit                 |
| <b>9420</b> | Power supply 24 V / 120 W - Ex nAC |