
PERFORMANCE MADE SMARTER



2-wire programmable transmitter

6334A


- TC input
- High measurement accuracy
- Galvanic isolation
- Programmable sensor error value
- 1- or 2-channel version

Application
- Linearized temperature measurement with TC sensor.
- Amplification of bipolar mV signals to a 4...20 mA signal, optionally linearized according to a defined linearization function.

Technical characteristics
- Within a few seconds the user can program PR6334A to measure temperatures within all TC ranges defined by the norms.
- Cold junction compensation (CJC) with a built-in temperature sensor.
- A limit can be programmed on the output signal.
- Continuous check of vital stored data for safety reasons.

Mounting / installation
- Mounted vertically or horizontally on a DIN rail. Using the 2-channel version up to 84 channels can be mounted per meter.
- The 6334A can be mounted in zone 2 and zone 22.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order

Type	Version		Galvanic isolation		Channels	
6334	Zone 2, 22 / Div. 2	: A	1500 VAC	: 2	Single Double	: A : B

Environmental Conditions

Operating temperature ..... -40°C to +85°C
Storage temperature ..... -40°C to +85°C
Calibration temperature ..... 20...28°C
Relative humidity ..... < 95% RH (non-cond.)
Protection degree IP20

Mechanical specifications

Dimensions (HxWxD) ..... 109 x 23.5 x 104 mm
Weight (1 / 2 channels) ..... 145 / 185 g
DIN rail type ..... DIN EN 60715/35 mm
Wire size ..... 0.13...2.08 mm^2 AWG 26...14 stranded wire
Screw terminal torque ..... 0.5 Nm

Common specifications

Supply

Supply voltage ..... 7.2...35 VDC
Max. required power ..... ≤ 0.8 W/≤ 1.6 W (1 ch./2 ch.)
Internal power dissipation ..... 0.17...0.8 W

Isolation voltage

Isolation voltage, test / working ..... 1.5 kVAC / 50 VAC

Response time

Response time (programmable) ..... 1...60 s
Voltage drop ..... 7.2 VDC
Warm-up time ..... 5 min.
Programming ..... PR 5909 Loop Link communications interface
Signal / noise ratio ..... Min. 60 dB
Accuracy ..... Better than 0.05% of selected range
EEprom error check ..... < 3.5 s
Signal dynamics, input ..... 18 bit
Signal dynamics, output ..... 16 bit
Effect of supply voltage change ..... < 0.005% of span / VDC
EMC immunity influence ..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst ..... < ±1% of span

Input specifications

Common input specifications

Max. offset ..... 50% of selected max. value

TC input

Thermocouple type ..... B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC) ..... < ±1.0°C

Voltage input

Measurement range ..... -12...150 mV
Min. measurement range (span) ..... 5 mV
Input resistance ..... Nom. 10 MΩ

Output specifications

Current output

Signal range ..... 4…20 mA
Min. signal range ..... 16 mA
Load (@ current output) ..... ≤ (Vsupply - 7.2) / 0.023 [Ω]
Sensor error indication ..... Programmable 3.5…23 mA
NAMUR NE43 Upscale/Downscale ..... 23 mA / 3.5 mA

Common output specifications

Updating time ..... 440 ms
of span ..... = of the presently selected range

Observed authority requirements

EMC 2014/30/EU
ATEX 2014/34/EU
RoHS 2011/65/EU
EAC ..... TR-CU 020/2011
EAC Ex ..... TR-CU 012/2011

Approvals

ATEX ..... DEKRA 20ATEX0096X
IECEx ..... DEK 20.0059X
INMETRO ..... DEKRA 23.0009X
EAC Ex ..... EAEU KZ 7500361.01.01.08756