



Pt100 temperature sensor

7400

- Accuracy, IEC 60751 class A
- Terminal head DIN 43729 form B
- 1/2" RG connection
- Stainless, acid-proof steel
- Protection tube $\varnothing 9 \times 1$ mm
- Temperature range -50°C to $+400^{\circ}\text{C}$

Application

- Temperature measurement in industrial systems, eg. in the food, chemical and pharmaceutical industries, cold storage plants, district heating, power plants, refineries and ships.
- Temperature measurement in gas and floating media.

Technical characteristics

- The 7400 comes with a fixed measurement insert.
- The sensor element is a thin film platinum resistor - Pt100 - trimmed at a laboratory to comply with the resistance values of the standard IEC 60751, class A. The advantage of a thin film element is an ultra short reaction time. The Pt100 element is electrically isolated from the protecting tube and terminal head.
- The protecting tube is $\varnothing 9 \times 1$ mm stainless, acid-proof steel W no. 1.4571 / AISI 316Ti, filled with aluminum oxide powder. A 1/2" RG thread nipple is welded on the protecting tube with a packing sheet of $\varnothing 30$ and span 30.
- The terminal head is a standard DIN 43729 form B housing produced in light-alloy metal, protected against corrosion through strong industrial lacquering.
- The sensor is available with or without cooling extension to keep the terminal head clear of isolated surfaces.


Electrical connection

- Each sensor is delivered with a three-wire connection which allows cable compensation to the sensor element.

Option

- Pt100 sensor type 7400 is available with a built-in ceramic socket (item no. 7423) or with a built-in 2-wire programmable transmitter for both standard and I.S. installations.

Applications



Order:

Type	Pt100 Sensors	Accuracy	Cooling extension	Insertion length
7400	1 x Pt100 : A	Class A : 1	None : A 100 mm : B	50 mm : 1 100 mm : 2 150 mm : 3 200 mm : 4 300 mm : 5 400 mm : 6

Environmental Conditions

Protection degree..... IP54

Mechanical specifications

Maks. tightening torque..... 50 Nm

Packing surface..... Ø 30 x Ø 21.5

Max. pressure for insertion

length > 250 mm..... 22.5 bar

Cable connection (screwed)..... M20 x 1.5

Width of flats..... 30

Common specifications

Recommended sensor current..... ≤ 2 mA

Max. temperature deviation

at 0°C..... ≤ ±0.15°C

Typical reaction time: water

with flow 0.2 m/s..... t0.5 after 20 s / t0.9 after 28 s

Typical reaction time: air

with flow 1 m/s..... t0.5 after 60 s / t0.9 after 180 s