PERFORMANCE MADE SMARTER



Universal uni-/bipolar signal transmitter

4104

- Measures and outputs uni-/bipolar voltage and current signals
- Works with both passive and active inputs and outputs
- Uses the PR 4500 display series for programming and process monitoring
- Fast < 20 ms response time and excellent < 0.05% accuracy
- Universally powered by 21.6…253 VAC / 19.2...300 VDC

Application

- Fast < 20 ms response time for measuring signals produced by torque, position, current & acceleration sensors.
- User configurable bipolar or unipolar I/O means the 4104 is suitable for nearly any voltage or current conversion.
- The excitation source enables measurement of two or three wire transmitters.
- The active or passive I/O makes the 4104 perfect for power matching current loops.
- Converts narrow bipolar inputs to wide bipolar or unipolar outputs, e.g., ±1 volt input = ±10 volt or 4...20 mA output.
- Selectable direct or inverse I/O makes the 4104 suitable for proportional control applications.
- The "V-curve" function outputs 100% – 0 – 100% when a 0 – 100% input signal is present.

Technical characteristics

- The latest analog and digital techniques are used to obtain maximum accuracy and immunity to interference.
- The current output can drive up to 800 Ohms, with an adjustable response time of 0.0…60.0 seconds.
- Exceptional mA output load stability of < 0.001% of span/100 Ohm.
- Meets the NAMUR NE21 recommendations, ensuring high accuracy in harsh EMC environments.
- Meets the NAMUR NE43 recommendations, allowing the control system to easily detect a sensor error.
- Each unit is tested to a high 2.3 kVAC, 3-port galvanic isolation level.
- Excellent signal to noise ratio of > 60 dB.

Mounting / installation / programming


- Very low power consumption means units can be mounted side by side without an air gap – even at 60°C ambient temperature.
- Approved for marine applications.
- Configuration, monitoring, 2-point process calibration and more are accomplished using PR's 4500 series of detachable displays.
- All programming can be password protected.

Note


- If you need an installation instruction in hard copy, you can order it for free when placing your order.

Applications


Input signals



Output signals



Supply



Safe Area or
Zone 2 / Cl. 1, Div. 2, gr. A-D

This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type
4104

Environmental Conditions

Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +85°C
Calibration temperature	20...28°C
Relative humidity	< 95% RH (non-cond.)
Protection degree	IP20
Installation in	Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)	109 x 23.5 x 104 mm
Weight approx	155 g
Weight incl. 4501 / 451x (approx.)	170 g / 185 g
DIN rail type	DIN EN 60715/35 mm
Wire size	0.13...2.08 mm^2 AWG 26...14 stranded wire
Screw terminal torque	0.5 Nm
Vibration	IEC 60068-2-6
2...13.2 Hz	±1 mm
13.2...100 Hz	±0.7 g

Common specifications

Supply

Supply voltage, universal	21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Max. required power	≤ 2.5 W
Max. power dissipation	≤ 2.5 W

Isolation voltage

Isolation voltage, test / working	2.3 kVAC / 250 VAC

Response time

Response time (0...90%, 100...10%)	< 20 ms

Auxiliary supplies

2-wire loop supply	> 16 V / 20 mA
3-wire loop supply	> 18 V / 20 mA
Loop supply limitation	30 mA
Programming	PR 4500 communication interfaces
Signal / noise ratio	> 60 dB
Cut-off frequency (3 dB)	> 40 Hz
Accuracy	Better than 0.05% of selected range
EMC immunity influence	< ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst	< ±1% of span

Input specifications

Current input

Signal range	±23 mA
Programmable measurement ranges	0...20 and 4...20 mA
Programmable measurement ranges	± 10 and ± 20 mA
Input voltage drop	1.4 V @ 20 mA
Loop error detection, 4...20 mA: Low	< 3.6 mA
Loop error detection, 4...20 mA: High	> 21 mA

Voltage input

Signal range	±12 V
Programmable measurement ranges	0/0.2...1, 0/1...5, 0/2...10 VDC
Programmable measurement ranges	±1, ±5 and ±10 V
Input resistance	> 2 MΩ

Output specifications

Current output

Signal range	0...23 mA (unipolar)
Signal range	-23...+23 mA (bipolar)
Current limit	≤ 28 mA (unipolar)
Current limit	± 28 mA (bipolar)
Load stability	≤ 0.001% of span / 100 Ω
Response time, programmable	0.0...60.0 s
Output limitation, on 4...20 and 20...4 mA signals	3.8...20.5 mA
Output limitation, on other unipolar mA signals	0 and 115% of max. value
Output limitation, on bipolar mA signals	±115% of min. & max. values
Sensor error indication, at 4...20 mA input: selectable	Low, High, Zero, None

Active unipolar and bipolar mA output

Programmable ranges	0...20 and 4...20 mA
Programmable ranges	±10 and ±20 mA
Programmable ranges	Direct or Inverted Action
V-curve function, active signals, 100-0-100%	20-0-20 mA
Load (@ current output)	≤ 800 Ω

Passive 2-wire mA output

Programmable ranges	0...20 and 4...20 mA
Programmable ranges	Direct or Inverted action
V-curve function, 100-0-100%	20-0-20 mA
External loop supply	3.5 - 26 V

Voltage output

Programmable signal ranges	0/0.2...1; 0/1...5 ; 0/2...10 V
Programmable signal ranges	±1, ±5 and ±10 V
Programmable signal ranges	Direct or Inverted action
V-curve function, 100-0-100%	1-0-1, 5-0-5 and 10-0-10 V
Load (@ voltage output)	≥ 500 kΩ
Response time, programmable	0.0...60.0 s
Output limitation - outside range: on unipolar V signals starting from 0	0 and 115% of max. value
Output limitation - outside range: on unipolar V signals with offset	-5% of min. value and 115% of max. value
Output limitation - outside range: on bipolar V signals	±115% of min. & max. values
Sensor error indication, at 4...20 mA input: selectable	Low, High, Zero, None

Observed authority requirements

EMC	2014/30/EU & UK SI 2016/1091
LVD	2014/35/EU & UK SI 2016/1101
RoHS	2011/65/EU & UK SI 2012/3032
EAC	TR-CU 020/2011

Approvals

c UL us, UL 508	E248256
FM	3025177
DNV Marine	TAA0000101