
PERFORMANCE MADE SMARTER



Isolated converter

3105

– Isolation and conversion of standard DC signals
– Response time < 7 ms
– DIP switch configuration
– Low cost
– Slimline housing of 6.1 mm


Functional highlights
- Galvanic separation of analog current and voltage signals.
- A competitive choice in terms of both price and technology for galvanic isolation of all signal types to SCADA systems or PLC equipment.
- High 3-port isolation provides surge suppression that protects the control system from transients and noise and eliminates ground loops.
- All terminals are over-voltage protected, polarity protected and short-circuit protected.
- Approved for marine applications.

Technical highlights
- Flexible 24 VDC (±30%) supply via power rail or connectors.
- Factory-calibrated measurement ranges.
- Fast response time < 7 ms.
- Excellent signal/noise ratio > 60 dB.
- High galvanic isolation of 2.5 kVAC.
- Inputs and outputs are floating and galvanically separated.
- A green front LED indicates normal operation and malfunction.

Programming
- Easy configuration via DIP switches.

Mounting / installation
- The narrow 6.1 mm housing allows up to 163 units per meter.
- Units can be mounted side by side, horizontally and vertically, without air gap on a standard DIN rail, even at 70°C ambient temperature.
- Units can be supplied separately or installed on PR 9400 power rail.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order

Type	Version	
3105	With power rail connector / terminals	: -
	Supplied via terminals	: -N

Example: 3105-N

Environmental Conditions

Operating temperature	0°C to +70°C
Storage temperature	-40°C to +85°C
Calibration temperature	20...28°C
Relative humidity	< 95% RH (non-cond.)
Protection degree	IP20
Installation in	Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)	113 x 6.1 x 115 mm
Weight approx.	70 g
DIN rail type	DIN EN 60715/35 mm
Wire size	0.13...2.5 mm^2 / AWG 26...12 stranded wire
Screw terminal torque	0.5 Nm
Vibration	IEC 60068-2-6
2...25 Hz	±1.6 mm
25...100 Hz	±4 g

Common specifications

Supply

Supply voltage	16.8...31.2 VDC
Max. required power	0.80 W
Max. power dissipation	0.52 W

Isolation voltage

Isolation voltage, test / working	2.5 kVAC / 300 VAC (reinforced)

Response time

Response time (0...90%, 100...10%)	< 7 ms
Programming	DIP switches
Signal / noise ratio	> 60 dB
Cut-off frequency (3 dB)	> 100 Hz
Signal dynamics, input	Analog signal chain
Signal dynamics, output	Analog signal chain
Accuracy	Better than 0.2% of selected range
Temperature coefficient	< ±0.015% of span / ˚C
EMC immunity influence	< ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst	< ±1% of span

Input specifications

Current input

Measurement range	0...23 mA
Programmable measurement ranges	0...20 and 4...20 mA
Input voltage drop	< 1.5 VDC
Input resistance	Nom. 20 Ω + PTC 50 Ω

Voltage input

Measurement range	0...10.25 V
Functional range	0...11.5 V / 0...5.75 V
Programmable measurement ranges	0/1...5 and 0/2...10 V
Input resistance	≥ 500 kΩ

Output specifications

Current output

Signal range	0...23 mA
Programmable signal ranges	0 / 4...20 mA
Load (@ current output)	≤ 600 Ω
Load stability	≤ 0.002% of span / 100 Ω
Current limit	≤ 28 mA

Voltage output

Signal range	0...10 VDC
Programmable signal ranges	0/1...5 and 0/2...10 V
Load (@ voltage output)	≥ 10 kΩ
of span	= of the DIP switch selected output range

Observed authority requirements

EMC	2014/30/EU & UK SI 2016/1091
LVD	2014/35/EU & UK SI 2016/1101
RoHS	2011/65/EU & UK SI 2012/3032
EAC	TR-CU 020/2011

Approvals

c UL us, UL 61010-1	E314307
DNV Marine	TAA00001RW