

Loop-powered LCD indicator

5531B



- 4 digit 1/8 DIN (48 x 96 mm) loop-powered LCD display
- Easy push-button configuration
- Backlit LCD display is readable in low light conditions
- Display can be mounted in the safe area or in I.S. / Ex zone 1



Application

- The 5531B indicator is powered by the 4 to 20 mA current loop and is easily scaled to display the correct process value.
- Because it does not require separate power wiring, the 5531B is perfect for remote display of process loops.
- The 5531B can be mounted in Ex Zone 1.

Technical characteristics


- With a full measurement range of 3.6 to 23 mA, the 5531B is NAMUR NE43 compliant.
- The display can be push-button scaled to any range between -9999 to 9999, and reverse display action is possible.
- The LCD backlight can be set to half or full intensity for easy viewing in low light conditions.
- The display only requires 1.5 VDC, (75 Ω loop load), with the backlight turned off.
- The input is HART transparent.
- The front push-buttons can be disabled to prevent unauthorized adjustment.

Mounting / installation

- Once panel mounted with the included gasket, the 5531B provides IP65 ingress protection.

Applications

Input signal:



Order

Type	Version
5531B	Zone 1, 2

Environmental Conditions

Operating temperature.....	-20°C to +60°C
Storage temperature.....	-20°C to +60°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP65, from front

Mechanical specifications

Dimensions (HxWxD).....	48 x 96 x 120 mm
Cut out dimensions.....	44.5 x 91.5 mm
Weight approx.....	200 g
Wire size, connector terminal	
1 - 4.....	0.13...2.08 mm ² / AWG 26...14 stranded wire

Common specifications

Supply

Supply voltage.....	Input loop-powered
---------------------	--------------------

Response time

Response time (0...90%, 100...10%).....	< 1 s
EMC immunity influence.....	< ±0.5% of span
Signal / noise ratio.....	> 60 dB
Updating time.....	500 ms

Input specifications

Current input

Measurement range.....	3.6...23 mA
Loop error detection, 4...20 mA: Low.....	~ < 3 mA
Loop error detection, 4...20 mA: High.....	~ > 24 mA
Input voltage drop, without backlight.....	< 1.5 V @ 20 mA
Input voltage drop, with half backlight.....	< 6.5 V @ 20 mA
Input voltage drop, with full backlight.....	< 10.5 V @ 20 mA

Output specifications

Display

Display readout.....	± 9999 (4 digits)
Digit height.....	16 mm

Observed authority requirements

EMC.....	2014/30/EU
ATEX.....	2014/34/EU
RoHS.....	2011/65/EU
EAC.....	TR-CU 020/2011
EAC Ex.....	TR-CU 012/2011

Approvals

ATEX.....	KEMA 05ATEX1105X
IECEX.....	DEK 24.0002X
CCC.....	2024322309006239
EAC Ex.....	EAEU KZ 7500361.01.01.08756