UNITED KINGDOM CONFORMITY ASSESSMENT

CERTIFICATE

(1) Type Examination

- (2) Product or Protective System intended for use in potentially explosive atmospheres - UKSI 2016:1107 (as amended) - Schedule 3A, Part 6
- (3) Type Examination Certificate Number: **DEKRA 21UKEX0173X** Issue Number: **0**
- (4) Product: HART-Transparent Driver, Types 9107BA, 9107BB and Types 9107AA, 9107AB
- (5) Manufacturer: **PRelectronics A/S**

DEKRA FKLA DEKRA

- (6) Address: Lerbakken 10, 8410 Rønde, Denmark
- (7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- (8) DEKRA Certification B.V., certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Schedule 1 of the Regulations 2016, UKSV 2016/1107 (as amended).

The examination and test results are recorded in confidential report NL/DEK/ExTR11.0102/03.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

```
EN IEC 60079-0 : 2018 /// EN 60079-7/: 2015/+ A1/: 2018 /// // EN IEC 60079-15 : 2019
```

except in respect of those requirements listed at item 18 of the Schedule to this certificate

- (10) If the sign "X" is placed after the certificate number, /t/ indicates that/the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.
- (11) This Type Examination Certificate relates only to the design and construction of the specified product and not to the manufacturing process and its monitoring.
- (12) The marking of the product shall/include the following



Date of certification: 9 June 2022

DEKRA Certification B.V.

R. Schuller Certification Manager

2716:3 Page 1/3

[®] Integral publication of this certificate and adjoining reports is allowed. This certificate and its schedules may only be reproduced in its entirety and without change.

DEKRA Certification B.V. Meander 1051, 6825 MJ Arnhem P.O. Box 5185, 6802 ED Arnhem The Netherlands T +31 88 96 83000 F +31 88 96 83100 www.dekra-product-safety.com Registered Arnhem 09085396



(13) SCHEDULE

(14) to Type Examination Certificate DEKRA 21UKEX0173X

Issue No. 0

(15) **Description**

HART-Transparent Drivers, Types 9107BA, 9107BB and Types 9107AA, 9107AB for rail mounting, are 24 V powered isolating barriers that serve as current output isolators for 4 - 20 mA signals with HART communication.

The HART-Transparent Driver, Types 9107BA, 9107AA are one channel version and Types 9107BB, 9107AB are two channel version.

The Driver provides a potential free contact for status indication.

The Driver is supplied via terminals at the front of the module, or via Power Rail Type 9400. Removable display module 4501 can be used for programming of the Driver.

Ambient temperature range -20 °C to +60 °C.

Electrical data

All Repeater Types

Supply (terminals 31, 32 and rear contacts): U = 19,2 ... 31,2 Vdc.

Status-Relay output (terminals 33, 34): $U \le 32$ Vac or 32 Vdc, $I \le 0.5$ Aac or $I \le 1$ Adc respectively. If the Driver is installed outside the hazardous area, the following data for the relay contacts apply: $U \le 110$ Vdc or 125 Vac, $I \le 0.3$ Adc or $I \le 0.5$ Aac respectively.

Inputs (terminals 11, 12 resp. 13, 14): I = 4 ... 20 mA.

Installation instructions

The instructions provided with the product shall be followed in detail to assure safe operation.

(16) **Report Number**

NL/DEK/ExTR11.0102/03.

(17) **Specific conditions of use**

The HART-Transparent Driver shall be installed in a controlled environment with suitably reduced pollution, limited to pollution degree 2 or better.

The circuits shall be limited to overvoltage category I/II as defined in EN 60664-1.

The HART-Transparent Driver shall be installed in an enclosure in type of protection Ex n or Ex e, providing a degree of protection of at least IP54. Cable entry devices and blanking elements shall fulfil the same requirements.

Removable Display Module 4501, when connected to the HART Transparent Driver, may not be damaged and shall be free of dust and moisture.



(13) **SCHEDULE**

(14)	to Type Examination Certificate DEKRA 21UKEX0173X	Issue No. 0
(14)	to Type Examination Certificate DERICA 2TOREAUT/3A	15500 100.

(18) Essential Health and Safety Requirements

Covered by the standards listed at item (9).

(19) **Test documentation**

As listed in Report number NL/DEK/ExTR11.0102/03.