

CERTIFICATE OF COMPLIANCE

Certificate Number 20191017-E233311
Report Reference E233311-20190627
Issue Date 2019-OCTOBER-17

Issued to: PR ELECTRONICS A/S
LERBAKKEN 10
8410 ROENDE DENMARK

**This certificate confirms that
representative samples of**

PROCESS CONTROL EQUIPMENT FOR USE IN
HAZARDOUS LOCATIONS
REFER ADDENDUM PAGE FOR MODELS

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety:
Additional Information:

REFER ADDENDUM PAGE
See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20191017-E233311
Report Reference E233311-20190627
Issue Date 2019-OCTOBER-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Equipment for use in Unclassified Locations or Class I, Division 2, Groups A, B, C and D Hazardous Locations.

HART Transparent Repeater Model 9106A, followed by 1 or 2, followed by A or B, followed by -U9. May be supplied with optional display/programming module type 4501.

Associated Apparatus for use in Unclassified Locations or Class I, Division 2, Groups A, B, C and D Hazardous Locations.

HART Transparent Repeater Model 9106B, followed by 1 or 2, followed by A or B, followed by -U9, provides intrinsically safe outputs for use in Class I, Division 1, Groups A, B, C and D, Class II, Groups E, F and G, Class III Hazardous Locations when installed in accordance with manufacturer's control drawing no. 9106QU01. May be supplied with optional display/programming module type 4501.


UL 913 - Standard for Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations

UL121201 - Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations

CSA C22.2 NO. 60079-0 - Explosive Atmospheres — Part 0: Equipment — General Requirements

CSA C22.2 NO. 60079-11:14 - Explosive Atmospheres — Part 11: Equipment Protection by Intrinsic Safety "i"

CSA C22.2 No. 213-17 - Non-incendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Division 1 and 2 Hazardous (classified) Locations



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

